

TECHNICAL INFORMATION

INTERIOR-EXTERIOR P-8

Article code: 1003

REV.1/JUN-12

Plastic paint formulated with acrylic copolymers, titanium dioxide and top-quality fillers, which provides a great coverage and a washable matt finish. It stands out because of its extraordinary WHITENESS, as a result of a careful combination of fillers and extremely white pigments.

INSTRUCTIONS FOR USE

On new surfaces, its application will be made by thinning it with 10-20% of water for the first coat, depending on the absorption of the surface.

For the second coat, let it dry for about 4-5 hours and afterwards, apply the paint thinned with 5-10% of water.

On surfaces which already have a coat, remove the paint if it's in bad condition. Once removed, proceed like on a new surface.

Its application can be made with a brush, a roller or a spray gun.

Stir the content until it is perfectly homogeneous.

TECHNICAL FEATURES

Pigmentation	1 : 5
Binder %	10%
Viscosity, viscometer HAKKE VT-02 (2) at 20 °C .	80-90 Poises
Washability after 7-day drying on leneta PVC according to the standards DIN53778 with GARDNER brush	>10000 Cyclos
Solids content %	61,5
Brushability	Very good
Performance m² per Litre and coat	10 – 12
Elasticity	Good
Specific weight	1'53 kg/lt
Resistance to alkalis	Good
Covering power	Very good
Preservation in the packaging.	Perfect in its original container if properly sealed

It is recommended just for white or light colours (pastel)

Information stated on this document is the result of the tests carried out in our laboratory with the continuous aim to improve and provide our customers with the best service. However, we shall not be responsible for the inconveniences which may arise due to a wrong application of our products.