

TECHNICAL DATA SHEET

ANTI-CONDENSATION PAINT

Article code: 1004

Interior/exterior plastic matt paint. It is formulated with acrylic copolymers and empty glass microspheres, which are inert and insulating and provide it with outstanding properties:

Anti-condensation, it prevents mould growth, thermal insulation and it dampens sound.

MAIN FEATURES

- Thermal insulation: over 5°C (Applus test: 17/14877-1420)
- Anti-condensation
- Warm to touch
- Low density
- Silky look
- Easy application with brush and roller
- Low contraction

TECHNICAL FEATURES

Finish	Matt, slightly textured
Colour	White
Density	1,00-1,06 kg/L
Performance	8-10 m ² /L per coat
Paint thinner	Water
Drying	To the touch: 1 hour Repainting: after 6-8 hours
GARDNER washability	10.000 cycles (Test method according to the standard UNE 48.243 (84))
VOCs max. content	< 30 g/L
EU's maximum value for this product (cat. A/a): 30 g/l (2010)		

Both drying and performance may be affected by variations on temperature, moisture, thickness and, above all, surface condition.

Information stated on this document is the result of the tests carried out in our laboratory with the continuous aim to improve and provide our customers with the best service. However, we shall not be responsible for the inconveniences which may arise due to a wrong application of our products.

TECHNICAL DATA SHEET

ANTI-CONDENSATION PAINT

Article code: 1004

RECOMMENDED USE

- On walls where there is condensation that causes moisture.
- For thermal insulation on walls which are exposed to very high temperatures and/or strong variation of temperatures.
- To reduce sound reverberance in establishments, houses, etc.
- As thermal insulation for hot or cold-water pipes.

INSTRUCTIONS FOR USE

It can be applied with a brush or a roller.

Surfaces to be painted must be dry and free of dust, grease, etc.

For thermal insulation, a minimum of 3 coats are necessary to obtain the recommended thickness of 250-300 microns, which equals 4 m²/l. On new surfaces, for the first coat, the paint shall be thinned with maximum 5% of water, depending on the application method and the absorption of the surface. For the second coat, it is recommended to let it dry for about 6-8 hours and apply it without thinning. For the third coat, we will follow the same procedure and will let it dry for 6-8 hours and apply it without thinning.

It is advisable to prepare the surface to be painted by removing the residues of the old badly adhered paint and by repairing cracks or chips. To improve the final result, it is better to apply a first coat of Fondofix or a base of sealant varnish. After this primer, proceed like on a new surface.

Do not use mechanical shakers to mix the colour in case of making colours or when thinning the paint.

If used on metallic surfaces, it is necessary to apply an antioxidant primer first.

Stir the paint in the container until the product is perfectly uniform.

WARNINGS

Preserve the product in its original container, properly sealed and at a temperature over 5° C. Do not apply below that temperature or over 35°C.

Keep it out of reach of children. Do not empty residues into drains. Use just in places with good air circulation. In case of ingestion, please consult a doctor immediately and show him/her the label or the container.

Information stated on this document is the result of the tests carried out in our laboratory with the continuous aim to improve and provide our customers with the best service. However, we shall not be responsible for the inconveniences which may arise due to a wrong application of our products.