

## TECHNICAL INFORMATION

# MATT CHARTER with ANTI-MOULD

Article Code: 15xx

Plastic paint formulated with acrylic polymers. It has a great performance and a soft matt finishing suitable for any type of outside and inside surfaces. In its formulation it includes additives which provide it with protection against mould growth.

### MAIN FEATURES

- Very good adherence
- Excellent outdoors resistance
- Great elasticity

### TECHNICAL FEATURES

|                     |       |   |
|---------------------|-------|---|
| Finishing           | ..... | Matt  |
| Colour              | ..... | White and colours chart                               |
| Viscosity           | ..... | 2500-3500 cps at 25°C                                 |
| Density             | ..... | 1,50–1,60 kg/L (based on colour)                      |
| Performance         | ..... | 8 –12 m <sup>2</sup> /L                               |
| Paint thinner       | ..... | Water   |
| Drying              | ..... | By touch: 40-60 minutes.<br>Second coat after 4 hours |
| Washability GARDNER | ..... | 20.000 Cycles (DIN 53778 standard)                    |

**\*Classification of fire reaction B-s1.d0 according to the standard UNE EN 13501-1:2007+A1:2010**

Both drying and performance may be affected by variations on temperature, moisture, thickness and, above all, surface condition.

Information stated on this document is the result of the tests carried out in our laboratory with the continuous aim to improve and provide our customers with the best service. However, we shall not be responsible for the inconveniences which may arise due to a wrong application of our products.

## TECHNICAL INFORMATION

# MATT CHARTER with ANTI-MOULD

Article Code: 15xx

## USE INSTRUCTIONS

It may be applied with a brush, a roller or a spray gun.

Surfaces to be painted shall be dry and free of dust, oil, etc.

On new surfaces, for the first coat, the paint shall be thinned with 10-20% of water, depending on the application mode and the absorption capacity of the surface.

Before proceeding with the painting, it is recommended to get the surface ready by removing residues of bad adhered paint and by repairing cracks or chips. In order to improve the finishing, it is advisable to apply a first coat of Fondofix or a base sealant varnish. After that, apply the paint as on new surfaces.

If the surface presents mould contamination, it shall be removed before painting.

Stir the paint in the container until the product is perfectly uniform.

## WARNINGS

Preserve the product in its original container, properly sealed and at a temperature over 5° C. Do not apply below that temperature or over 35°C.

Keep it out of reach of children. Do not empty residues into drains. Use just in places with good air circulation. In case of ingestion, please consult a doctor immediately and show him/her the label or the container.

Information stated on this document is the result of the tests carried out in our laboratory with the continuous aim to improve and provide our customers with the best service. However, we shall not be responsible for the inconveniences which may arise due to a wrong application of our products.