

## TECHNICAL INFORMATION

### PROFESSIONAL SEMI-MATT

Plastic paint formulated with high-performance and extremely white vinylic copolymers. It provides a semi-matt finish suitable for protecting and decorating surfaces both inside and outside.

#### MAIN FEATURES

- It doesn't yellow
- Excellent weather resistance
- Very Good brushability and levelling

#### TECHNICAL FEATURES

Finish	.....	Semi-Matt
Colour	.....	White
Viscosity	.....	2300± 800 cps at 20°C
Density	.....	1,22-1.28 kg/L
Performance	.....	12-14 m <sup>2</sup> /L
Washability GARDNER	.....	>10.000 Cycles
Drying	.....	To the touch: 20-40 minutes. Second coat, after minimum 4 hours.

2004/42/IIA (c) (30) Max. COVs 30g/L

Both drying and performance may be affected by variations on temperature, moisture, thickness, surface condition, etc.

Information stated on this document is the result of the tests carried out in our laboratory with the continuous aim to improve and provide our customers with the best service. However, we shall not be responsible for the inconveniences which may arise due to a wrong application of our products.

## TECHNICAL INFORMATION

# PROFESSIONAL SEMI-MATT

## INSTRUCTIONS FOR USE

Its application can be made with a brush, a roller or a spray gun.

On new surfaces, its application will be made by thinning it with 10-20% of water for the first coat, depending on the application method and the absorption of the surface.

For the second coat, let it dry for about 4-5 hours and afterwards, apply the paint thinned with 5-10% of water.

On surfaces which already have a coat, remove the paint if it's in bad condition. Once removed, proceed like on a new surface.

Stir the content until it is perfectly homogeneous.

## WARNINGS

Preserve the product at a temperature over 5°C. Do not use below 5°C or over 35°C.

Keep it out of children's reach. Do not empty residues into drains. Use it just in places with good air circulation. In case of ingestion, seek medical advice and show the label or the container.

Information stated on this document is the result of the tests carried out in our laboratory with the continuous aim to improve and provide our customers with the best service. However, we shall not be responsible for the inconveniences which may arise due to a wrong application of our products.