

TECHNICAL INFORMATION

REV.1/FEB-07

SUPER SATIN PROFESSIONAL PLASTIC

Article code: 1981

Plastic paint formulated with high-performance and extremely white acryl-vinyl copolymers. It features a satin finish suitable for top decoration of all types of surfaces.

INSTRUCTIONS FOR USE

On new surfaces, for the first coat, the paint shall be thinned with 10% - 20% of water, depending on the absorption of the surface. For the second coat, let it dry for about 4-5 hours and apply it thinned with 5-10% of water.

On surfaces which already have a paint coat, remove the old paint if it's in bad condition and proceed like on new surfaces.

Its application can be made with a brush, a spray gun or a roller.

Stir the content until it is perfectly homogeneous.

TECHNICAL FEATURES

Pigmentation	1:1
Binder %	50
Viscosity, viscometer HAKKE VT-02(2)at 20° C	50-60 Poises
Washability GARDNER after 7-day drying on Leneta PVC panel according to the standards DIN 53778	50.000 Cycles
Solids content %	52
Weather resistance	Very good
Elasticity	Excellent
Brushability	Excellent
Performance	14 - 16 m ² / litre

Information stated on this document is the result of the tests carried out in our laboratory with the continuous aim to improve and provide our customers with the best service. However, we shall not be responsible for the inconveniences which may arise due to a wrong application of our products.