

TECHNICAL INFORMATION

BRIGHT ESTIL

Article code: 3100

It is a synthetic glossy enamel, suitable for protecting and decorating wood, metals and construction materials, both indoor and outdoor. It has a great brushability, very good levelling and covering. Its balanced formulation provides it with exceptional adhesion, hardness and elasticity, as well as with an ideal drying time.

MAIN FEATURES

- Low yellowing
- Excellent weathering resistance for outdoor
- Good resistance to abrasion

TECHNICAL FEATURES

Finish	Glossy
Colour	White and other chart colours
Density	1,00-1,20 kg/L depending on the colour
Viscosity	40-100 seconds, CF 6 at 20°
Performance	11 –13 m ² /L
Thinner	Turpentine or solvent for synthetic paint
Drying time (set-to-touch)	6 - 8 hours at 20°C
Repainting	After 24 hours
Drying time (total)	7 days

*** Reaction to Fire Classification Bs1.d0 (UNE EN 13501-1:2007+A1:2010)**

2004/42/IIA (d) (300) Max. COVs 300g/L

Both drying time and performance may be affected by variations on temperature, moisture, thickness and, above all, surface condition.

Information stated on this document is the result of the tests carried out in our laboratory with the continuous aim to improve and provide our customers with the best service. However, we shall not be responsible for the inconveniences which may arise due to a wrong application of our products.

TECHNICAL INFORMATION

BRIGHT ESTIL

Article code: 3100

USE INSTRUCTIONS

Bright Estil can be applied on wood and metal surfaces, as well as on any construction material in general. It can be applied with a brush, a roller or a spray gun. It is not necessary to think it for application with a brush or a roller. For application with a spray gun, it can be thinned with a 10-15% of Lepanto solvent for synthetic paint or turpentine.

For a perfect adhesion, new surfaces must be dry, free of dust and grease, and properly primed.

For painting surfaces which already have a coat on them, if paint is in good condition, they will have to be washed in depth and lightly sanded. If paint is bad adhered, it will have to be removed and proceed as on a new surface.

It is necessary to apply thin coats in order to achieve a proper drying.

Stir the paint until the whole content of the container is uniform.

WARNINGS

Preserve the product in its original container, properly sealed and at temperatures over 5°C. Do not apply below this temperature or over 35°C.

Flammable liquid and steam. Harmful in case of ingestion. It can be lethal in case of ingestion or penetration in the respiratory tract. Harmful in contact with skin. It causes serious ocular injuries. Harmful in case of inhalation. It may cause somnolence and vertigo. Very toxic for aquatic organisms with long-lasting effects. Recurrent exposure may cause skin dryness or cracking.

Keep it out of children's reach. Do not empty residues into drains. Use it just in places with good air circulation. In case of ingestion, seek medical advice and show the label or the container.

Information stated on this document is the result of the tests carried out in our laboratory with the continuous aim to improve and provide our customers with the best service. However, we shall not be responsible for the inconveniences which may arise due to a wrong application of our products.