

TECHNICAL INFORMATION

ESTIL-LAC

Article Code: 3101

It is a high-quality synthetic urethane enamel with a satin finish. It is ideal for lacquering any type of surface, both indoor and outdoor, specially furniture, doors, windows, radiators, etc.

It has a great performance and an outstanding covering obtaining a long-lasting decorative finish which is resistant to marks and scratches.

MAIN FEATURES

- Fast drying
- Excellent resistance to abrasion
- Great flexibility

TECHNICAL FEATURES

Finish	Satin
Colour	White, black and colours chart
Density	1,12-1,34 kg/L depending on the colour
Viscosity	40-100 seconds, CF 6 at 20°
Performance	10 – 12 m ² /L
Thinner	Turpentine or solvent for synthetic paint
Drying by touch	3 - 4 hours at 20°C
Repainting	at least after 10 hours
Total drying	7 days

2004/42/IIA (d) (300) Max. COVs 300g/L

Both drying and performance may be affected by variations on temperature, moisture, coat thickness and, above all, surface condition.

Information stated on this document is the result of the tests carried out in our laboratory with the continuous aim to improve and provide our customers with the best service. However, we shall not be responsible for the inconveniences which may arise due to a wrong application of our products.

TECHNICAL INFORMATION

ESTIL-LAC

Article Code: 3101

USE INSTRUCTIONS

Estil-LAC can be applied on wooden and metal surfaces, and, overall, on any construction material with a brush, a roller or a spray gun. It is a ready-to-use product. So, it does not have to be thinned.

For a perfect adhesion on new surfaces, they have to be clean, free of dust and grease, and properly primed.

For painting on already painted surfaces, if paint is in good condition, it will have to be washed in depth and lightly sanded. However, if paint is badly adhered, it is necessary to remove it and proceed as on a new surface.

It is necessary to apply thin coats in order to achieve a proper drying.

Stir the paint until the whole content of the container is uniform.

Lepanto solvent for synthetic paint or turpentine are recommended for cleaning the tools.

WARNINGS

Preserve the product in its original container, properly sealed, at a temperature over 5°C. Do not use below 5°C or over 35°C.

Flammable liquid and steam. Harmful in case of ingestion. It can be lethal in case of ingestion or penetration in the respiratory tract. Harmful in contact with skin. It causes serious ocular injuries. Harmful in case of inhalation. It may cause somnolence and vertigo. Very toxic for aquatic organisms with long-lasting effects. Recurrent exposure may cause skin dryness or cracking.

Keep it out of children's reach. Do not empty residues into drains. Use it just in places with good air circulation. In case of ingestion, seek medical advice and show the label or the container.

Information stated on this document is the result of the tests carried out in our laboratory with the continuous aim to improve and provide our customers with the best service. However, we shall not be responsible for the inconveniences which may arise due to a wrong application of our products.