

TECHNICAL INFORMATION

INDUSTRIAL BRIGHT WHITE ENAMEL

Quick dry and glossy finish industrial enamel which has been conceived to improve the protection and the finishing touch of metallic surfaces, especially iron ones.

MAIN FEATURES

- Excellent weathering resistance for outdoor
- Fast drying
- No yellowing

TECHNICAL FEATURES

Nature	Alkyd resin
Colour	White
Finish	Glossy
Density	1,30 ± 0,03 kg/L
Viscosity	55 ± 15 s, Copa Ford nº 6, at 20° C
Drying	15 min
Repainting	2-3 hours
Performance	8-10 m ² /L and coat
Thinner	Xylene or universal solvent
Thickness	50-60 µ.
Caution	See safety data sheet.

*Reaction to fire classification B-s1.d0, according to the standard UNE EN 13501-1:2007+A1:2010

Both drying time and performance may be affected by variations on temperature, moisture, thickness and, above all, surface condition.

Information stated on this document is the result of the tests carried out in our laboratory with the continuous aim to improve and provide our customers with the best service. However, we shall not be responsible for the inconveniences which may arise due to a wrong application of our products.

TECHNICAL INFORMATION

INDUSTRIAL BRIGHT WHITE ENAMEL

USE INSTRUCTIONS

Its application is carried out mainly with a spray gun and it can be thinned with 10-15% of xylene or universal solvent.

For a right application, surfaces must be clean, dry, free of grease and properly primed.

Stir the paint until the whole content of the container is uniform.

WARNINGS

This product must be preserved at a temperature over 5°C and must not be applied below this temperature or over 35°C.

Flammable. Recurrent exposure may cause skin dryness or cracking. Steam inhalation may cause somnolence and vertigo. Toxic for marine organisms. In the long term, it may cause negative effects on aquatic environments. Keep it out of children's reach. Avoid skin contact. Do not empty residues into drains. Get rid of this substance and its package in a public collection point for special or dangerous residues. Use it just in places with good air circulation. It contains 2-butanone-oxime, cobalt 2-ethylhexanoate. It may cause allergic reaction.

In case of ingestion, seek medical advice and show the label or the container.

Information stated on this document is the result of the tests carried out in our laboratory with the continuous aim to improve and provide our customers with the best service. However, we shall not be responsible for the inconveniences which may arise due to a wrong application of our products.