

TECHNICAL INFORMATION

REV.1/FEB-15

PLASTIC INT-EXT SPECIAL LANIUM

Article code: 19806

Plastic paint for professional use for the protection and decoration of all types of walls. It stands out because of its matt look, its whiteness and its great covering. No splatter.

INSTRUCTIONS FOR USE

On new surfaces, for the first coat, the paint shall be thinned with 10% - 20% of water, depending on the absorption of the surface. For the second coat, let it dry for about 4-5 hours and apply it thinned with 5-10% of water.

On surfaces which already have a paint coat, remove the old paint if it's in bad condition and proceed like on new surfaces.

Its application can be made with a brush, a spray gun or a roller.

Stir the content until it is perfectly homogeneous.

TECHNICAL FEATURES

Pigmentation	1:5
Binder %	9%
Solids content	62%
Viscosity, viscometer HAKKE VT-02(2) at 20°C	...	70-80 poises
Wet abrasion resistance after 7-day drying on Leneta PVC scrub panel with GARDNER brush	... > 7000 cycles	
Performance m2 per litre	8-10 m ² /lt/coat depending on surface
Brushability	Very good
Specific weight	1,52-1,54 kg/lt
Resistance to alkalis	Good
Coverage power	Good

Information stated on this document is the result of the tests carried out in our laboratory with the continuous aim to improve and provide our customers with the best service. However, we shall not be responsible for the inconveniences which may arise due to a wrong application of our products.